

Add recipient API – AddRecipient

- “add respondents to a panel”

Add recipient API is RESTful web-service, allows you to add one or more recipients to an existing e-mail or e-Boks panel.

Input

End point URL: <https://app.defgo.com/defgo/api/AddRecipient>

Protocol type: HTTP

Request method: POST

Request data type: JSON

Response data type: JSON

Parameters:

- “panelId”: <panel id, int>,
- “checksum”: <checksum, string>,
- “panelData”: <recipients list, string[][]>

Example:

- “panelId”: 12345,
- “checksum”: “ABCDEDEF”,
- “panelData”: [
 [“user1@gmail.com”, “user1 name”, “dep 1”, “manager”],
 [“user2@gmail.com”, “user2 name”, “dep 1”, “manager”]
]

Result/Output

If the request succeeds, the response code will be 200 and the “ids” field will contain an array with the ids of the added recipients. The “error” field will contain an empty string.

If the request fails because of incorrect data, the response code will be 500. The “error” field will contain a description of the error, and the “ids” field will contain an empty array.

If the request fails because of an incorrect method, header, or path, the error code may be different, and the response body may be missing.

Response body format:

- “error”: <error msg, string>, “ids”: <int[]>

Example:

- “error”: “”, “ids”: [4,5]
- “error”: “Incorrect data”, “ids”: []

Comments

- The checksum can be found in the properties of the panel
- Saving data is a lengthy process, so one query that adds many recipients will be more efficient than more small queries.